

ION 318

KARGO^{ION}



CE ISO9001

STANDARD EQUIPMENTS


Specifications

| | |
|------------------------------------|-----------------------------------|
| Rated capacity | 1750 kg with load center at 500mm |
| Travel speed (no load / full load) | 15/13.5 Km/h |
| Lift speed (no load / full load) | 0.47/0.30 m/s |
| Turning radius | 1500 mm |
| Max. gradeability | 19% |
| Mast tilt angle | 5/7 deg |
| Operational weight | 3260 kg |
| Front tires | 18X7-8PR |
| Rear tires | 16X6-8PR |
| Front wheel clearance | 895 mm |
| Rear wheel clearance | 205 mm |
| Wheelbase | 1295 mm |
| Overall length | 2830 mm |
| Overall width | 1050 mm |
| Overhead guard height | 1990 mm |
| Fork size | 920 mm |


Equipments



AC Power



- A/C Motor
- Hydrostatic power steering
- Ergonomical levers
- LCD digital contrôle display
- Wheel position indicator
- Adjustable steering column
- Kargo suspension seat with back rest adjustment and selt belt
- Amenity tray
- Handbrake
- Rear lighting
- 2 front working lamps
- Engine hood assisted opening
- Easy access handle to the driving station
- Diabolo-type rear wheels





ION 318

KARGO ION®

CE ISO9001

DIAGRAMS

