

TH 15**KARGOTH**

CE ISO9001

STANDARD EQUIPMENTS**Engine**

Rated capacity	1500 kg with load center at 500mm
Manufacturer / type	ISUZU / C240PKJ
Energy / capacity	Diesel / 2,37 L
Rated output	34.5 Kw / 2500tr/mn
Rated torque	139 Nm / 1800 tr/mn
Transmission	TCM Converter

Specifications

Travel speed (no load / full load)	14.5/13.5 Km/h
Lift speed (no load / full load)	0.51/0.45 m/s
Turning radius	1960 mm
Max. gradeability	20%
Mast tilt angle	6/12 deg
Operational weight	2740 kg
Front tires	6.50-10-10PR
Rear tires	5.00-8-10PR
Front wheel clearance	890 mm
Rear wheel clearance	920 mm
Wheelbase	1400 mm
Overall length (without fork)	2235 mm
Overall width (wheel width)	1095 mm
Overhead guard height	2075 mm
Fork size	920 mm

Driving station

- Hydrostatic power steering
- Ergonomical levers
- Numerical hourmeter
- Permanent fuel gauge
- Engine oil pressure warning light
- Alternator charge warning light
- Tilt steering column
- Kargo suspension seat with back rest adjustment and seat belt
- Amenity tray
- Handbrake
- Rear lighting
- 2 front working lamps
- Engine hood assisted opening
- Easy access handle to the driving station

**Performance**

Industrial engine designed and manufactured by
Easy maintenance

ISUZU


TH 15

KARGOTH



CE ISO9001

DIAGRAMS



Available mast for KARGO TH15

		Lift height	Mast lowered height	Free lift height	Mast extended height
DOUBLE MAST	full mast	VM300 : 3000mm	1996mm	164mm	3545mm
		VM330 : 3300mm	2146mm	164mm	3845mm
		VM350 : 3500mm	2246mm	164mm	4045mm
		VM400 : 4000mm	2546mm	164mm	4545mm
		VM450 : 4500mm	2796mm	164mm	5045mm
		VM500 : 5000mm	3046mm	164mm	5545mm
		VM550 : 5500mm	3346mm	164mm	6045mm
		VM600 : 6000mm	3596mm	164mm	6545mm
DOUBLE MAST	full free mast	VFM300 : 3000mm	1996mm	1481mm	3555mm
		VFM330 : 3300mm	2146mm	1631mm	3855mm
		VFM350 : 3500mm	2246mm	1731mm	4055mm
		VFM400 : 4000mm	2546mm	2031mm	4555mm
TRIPLE MAST	full free mast	VFHM400 : 4000mm	1930mm	1415mm	4545mm
		VFHM435 : 4350mm	2055mm	1540mm	4895mm
		VFHM450 : 4500mm	2105mm	1590mm	5045mm
		VFHM480 : 4800mm	2205mm	1690mm	5345mm
		VFHM500 : 5000mm	2305mm	1790mm	5545mm
		VFHM540 : 5400mm	2430mm	1915mm	5945mm
		VFHM600 : 6000mm	2655mm	2140mm	6545mm

Others masts are available, contact us.

* Mast extended height + 485mm if equiped with backrest